

Enclosure Type:	Type B - GE
Listing Agency:	Intertek-ETL
Designations:	50kVA 1-PHASE (TYPE B-GE)
kVA:	50
Primary:	480V
Secondary:	120/240V
Primary MCB Disconnect:	-
Frequency:	60 Hz
Sound Level:	30 dB Max.
BIL:	5kV+
Insulation Class:	F (155° C)
Leads:	Fine Stranded, Copper, Tin-Plated
Temperature Rise (80% Load):	60° C
Impedance:	2.2% - 3.5%

Terminations	Location	Terminals
Primary:	Front	(2) 350MCM / PHASE
Secondary:	Front	MCB or MLO

Estimated Weight:	1130
Base Height:	12" (Requires No Extra Curbing)
Base Mounting Isolation:	45 Durometer .25" Thick Neoprene Rubber
Gland Plate Dimensions:	11" x 39"
Housing Material:	316L Stainless Steel (NEMA 3R)
Housing Coating:	White Powder Coat
Cooling:	Eight (8) Internal, Thermo-Statically Controlled Fans. Thermostat Closes at 140° F
Condensation Removal:	Photocell Controlled Fans
Lifting:	Engineered Swivels Concealed Under Removable Solar Shield. Tested to Exceed 4520 lbs. Capacity Minimum (4x Static Weight)
Forklift Access:	Front / Side

Wiring Connections:


**PRIMARY:** H1, H2  
**SECONDARY:** X0, X1, X2, (X0 is Neutral)  
 Wired to Main Circuit Breaker / Main Lug

MARINA ELECTRICAL EQUIPMENT, INC.

100 WARWICK COURT  
 WILLIAMSBURG, VA 23185

TEL: 1-855-259-3939  
 FAX: 757-259-9888

WEB: www.marinaelectricequipment.com



NO.	REVISION	DATE

DATE: 10/09/14

DRAWN: CLD CHECKED: KWT

SCALE: NTS

GTX UNIT SUBSTATION

50kVA  
 1-PHASE  
 TYPE B-GE  
 SHEET